

AeGIS 9000 Series MULTI-TENANT DEDICATED PHONE LINE SYSTEM

- PROGRAMMABLE HANDS FREE SYSTEM
- MANAGEMENT SOFTWARE INCLUDED
- 1200 EVENT ACTIVITIES REPORT
- 26 WIEGAND INPUT FOR PROXIMITY READER
- POSTAL LOCK READY
 CELLULAR PHONE COMPATIBLE
- TWO LINES BACKLIT ELECTRONIC DIRECTORY
- BUILT-IN NIGHT LIGHTS
 BUILT-IN MODEM
- DOUBLE RELAY WITH INDEPENDENT STRIKE
- 10 TIME ZONES
 16 HOLIDAY TIME ZONES
 10 AUTO UNLOCK TIMER SCHEDULES
- BRUSH STAINLESS STEEL FACE-PLATE



SPECIFICATIONS		Satellite Systems
SPECIFICATIONS	ORDERING PART	SCR9 Satellite Card Reader
POWER INPUT: 12VAC/40VA (supplied) or	Surface Mount	SK9 Satellite Keypad
12VDC/40VA (9100CR200 100 tenants 200 cards/codes	SK9M RS-485 module Prox-Readers, AWRR
output reading must be 13.5 - 14.5 VDC).	9250CR1000 250 tenants 1000 cards/codes	and AFGR9.
CURRENT CONSUMPTION: 700mA idle,	9500CR1000 500 tenants 1000 cards/codes	Pedestal Mounting Post, Adapter Plate and
900mA operating.	91KCR1000 1000 tenants 1000 cards/codes	Mounting Ring
EMERGENCY BATTERY: Built-in charging cir-		APM1 Pedestal Mounting Post.
cuit for 12VDC/4Ahr rechargeable battery (bat-		APMDB1 Direct Burial Pedestal Mounting
tery is not supplied).	9250CR1000 250 tenants 1000 cards/codes	Post.
OPERATING ENVIRONMENT: 32°F to 140°F.	9500CR1000 500 tenants 1000 cards/codes	APM2 Double arm mounting base plate.
Humidity 0%-95% noncondensing. Heater is	91KCR1000 1000 tenants 1000 cards/codes	APM3 Pedestal mounting post for semi-truck.
required if the temperature is below 32°F.		APM5 Double arm side by side mounting base
ELECTRONIC DIRECTORY: 2x16 Backlit	ACCESSORIES	plate.
Liquid Crystal Display (LCD).	26-Bit Wiegand Proximity Readers and cards	AP9 Adapter Plate for APM1, APM2, APM3,
DIALING: Tone.	AWCR Wiegand Proximity Reader.	APM4 and APM5.
NIGHT LIGHT: Super Bright Light Emitting	AWCRS Small Wiegand Proximity Reader.	<u>Video Package</u>
Diode (LED).	AWCRL Long Range Proximity Reader.	AVPC AeGIS Color Video Package.
MEMORY: EEPROM (non-volatile).	AWCRSL Super Long Range Proximity	Miscellaneous Accessories
CLOCK BATTERY BACKUP: Ni-Cd 3.6V	Reader.	AP9 Adapter Plate for APM1, APM2, APM3,
60mAh.	AISO credit card size (passive card)	APM4 and APM5.
COMMUNICATION: 1200 Baud Modem, RS-	ACLAM Clam Shell (passive card)	FFM9 Full-flush mounting ring, is included w/
485 and RS-232.	AFOB Key Fob (passive fob)	system
CONSTRUCTION: 16 Gauge Cold Rolled	ALRPC5 26 Bit Wiegand (active Card)	ASP1 AC and Telephone Surge Protector.
Steel back box with enamel finished and Brushed Stainless Steel	ALRPC7 26 Bit Wiegand (active Card)	AHP5 Heater Pad with Thermostat.
	Biometric Finger Print with 26-Bit Wiegand	ABAT1 12VDC 4.5 Ahr backup battery. ABHSE9 Battery Housing.
Faceplate MOUNTING: Surface and full-flush.	<u>Output</u>	ARIGB9 Rough-in box.
DIMENSIONS:	AFGR9 Biometric Finger Print Reader	
<u>Surface</u> 13-9/16"(H) x 11-1/4"(W) x 3-3/4"(D)	26-Bit Wiegand Radio Receiver and	
$\frac{\text{Sundee}}{\text{Full-flush}} 13-7/8" (H) \times 11-9/16"(W) \times 3-3/4"$	<u>Transmitters</u>	
(D)	AWRR Radio Reader Receiver.	
MOUNTING RING FULL-FLUSH (FFM9 is	AFOBT Single Button Keyfob Transmitter.	
included):	AFOBT2 Two Button Keyfob Transmitter.	
Inside 13-3/4" (H) x 12" (W) x 3-11/16" (D)	AHHT Single Button Handheld Transmitter.	
<u>Outside</u> 18" (H) x 15-5/8" (W)	AHHT2 Two Button Handheld Transmitter.	
WARRANTY: Two years (24 months)		
		Specifications subject to change without prior notice.
AeGIS ACCESS CONTROL	941 Calle Negocio	Phone: 888-678-7224
www.pach-co.com	San Clemente, CA 92673	Fax: 949-498-6879