

### FEATURES

- One Momentary-Action, Push-Button Switch
- Constructed of Rugged Stainless Steel
- Attractive Brushed Finish
- Standard 2-Gang Configuration
- Flush or Surface Mounting
- Built-in, line matching transformer

### DESCRIPTION

The Telecor IC-1 Intercom Station is designed for use with Telecor Communication Systems. The station is equipped with a momentary action, pushbutton switch for initiating call-ins.

The unit is inscribed with the letters "Push to Call" on the stainless steel faceplate.

The IC-1 is equipped with a 2" permanent magnet loudspeaker and 25 Volt audio distribution transformer. The unit mounts on a standard 2-gang electrical box, either flush or surface mount.

### ARCHITECT'S & ENGINEER'S SPECIFICATIONS

The intercom station shall be a Telecor Model IC-1 or approved equal supplied and installed as indicated on the plans.

The intercom station shall be equipped with a momentary action, pushbutton switch used to initiate calls.

All components shall be mounted on a sub-chassis beneath the 2-gang stainless steel plate. No mounting holes or fasteners shall be visible with the exception of the 4 mounting holes used to fasten the station to the backbox. The station shall be equipped with a 2" loudspeaker and 25 Volt audio distribution transformer.

The station shall be suitable for flush mounting to a standard 2-gang backbox with 3-9/32" mounting centres.

### IC-1 SPECIFICATIONS

Weight:	9 oz. (253 g)
Finish:	Brushed stainless steel
Terminations:	IDC @ .156" centers
Wiring req:	2-pair, AWG 22 (one pair twisted, shielded)
Speaker	2" permanent magnet
Transformer:	25 Volt line, 0.5 Watt
Switch:	1-position momentary action, pushbutton contact type
Dimensions:	4-1/2"H x 4-1/2"W x 1-1/2" D
Backbox req:	2-gang, 2" D with 3-9/32" mounting centers

### PARTIAL LIST OF ASSOCIATED EQUIPMENT

All Telecor Communication Systems

All product information subject to change without notice.

