

NEW!

VISTA-250BP

The new VISTA-250BP is an eight partition, 250 zone UL commercial burglary control panel that meets the demanding requirements of today's commercial installations while simplifying end-user operation.

A revolutionary new feature called **PANEL LINKING** allows multiple partitions, panels – even buildings – to be armed, disarmed and have status checked all from one location. Up to eight VISTA-250BP panels can be linked together, and the control can be integrated with ADEMCO's PassPoint system (via the VISTA Gateway Module) to provide a fully integrated security and access control system. The VISTAKey Access Control system and the VISTAView-100 CCTV Switcher can also be seamlessly integrated with this powerful commercial platform.



**Commercial
Burg/CCTV and
Access Control
Platform**

FEATURES:

- Provides nine style-B hardwired zones
- Supports up to 241 additional zones using a built-in polling (multiplex) loop interface
- Supports up to 250 wireless zones using 5881 type RF receiver (fewer if using hardwired and/or polling loop zones)
- Provides 1 power-limited bell circuit delivering 1.7Amp (max) at 12Vdc.
- Provides the ability to control eight separate partitions independently, each functioning as if it had its own separate control
- Accommodates 250 user codes with seven authority levels
- Accommodates 32 keypad macro commands per system
- Keeps a log of up to 1,000 events
- VISTAView-100 CCTV support
- Supports up to 16 two-wire smoke detectors on zone 1
- Supports up to 50 latching-type glassbreak detectors on zone 8
- Zone 7 may be used for keyswitch arming/disarming
- Integrates with PassPoint access control systems to provide increased users, event log, and scheduling (up to 32 doors)
- Supports **VALET** addressable VISTAKey access control (up to 15 doors and 500 cards)
- Easily programmed and maintained by the newly upgraded Compass Windows-based downloader
- Supports up to 96 programmable relays
- Supports the ADEMCO 4286 VIP Module
- False alarm reduction features

New Enhancement:

• **PANEL LINKING** up to eight panels

- Two-Way RS232 (facility automation software support) optional
- Supports eight numeric pager numbers
- Supports touch screen Advanced User Interface (AUI) (Future)
- Smoke Detector Reset at keypad
- QUICK EXIT
- Group Bypass
- Arm Faulted
- Event Arming
- Scheduled check-in
- ARM STAY by group

**ADEMCO
GROUP**